

**IEC****IECEE**

®

TM

Ref. Certif. No.

CN52071

IEC SYSTEM FOR MUTUAL RECOGNITION OF TEST CERTIFICATES FOR ELECTRICAL EQUIPMENT  
(IECEE) CB SCHEME**CB TEST CERTIFICATE**

Product

Moulded Case Circuit-breakers

Name and address of the applicant

NOARK ELECTRIC USA INC.  
2188 Pomona Blvd. Pomona, CA 91768-3322, USA

Name and address of the manufacturer

NOARK Electrics (Shanghai) Co., Ltd.  
No.3857 Sixian Road, Songjiang District, Shanghai,  
P.R.China

Name and address of the factory

NOARK Electrics (Shanghai) Co., Ltd.  
No.3857 Sixian Road, Songjiang District, Shanghai, P.R.China*Note: When more than one factory, please report on page 2*

Ratings and principal characteristics

See the Appendix

Trademark / Brand (if any)

NOARK

Customer's Testing Facility (CTF) Stage used

Model / Type Ref.

BIN, BIH

Additional information (if necessary may also be reported on page 2)

IEC 60947-2:2016(5th Edition); IEC  
60947-2:2016/AMD1:2019

A sample of the product was tested and found to be in conformity with

00901-CB2020CQC-091501

As shown in the Test Report Ref. No. which forms part of this Certificate

This CB Test Certificate is issued by the National Certification Body

**CHINA QUALITY CERTIFICATION CENTRE**Section 9, No. 188 Nansihuan Xilu, Beijing 100070 P. R. China  
Tel: +86-10-83886666 Fax: +86-10-83886282  
website: <http://www.cqc.com.cn>

Date: Dec.07,2020

Signature:

Lu Mei

**CB 0059430**

B1N, B1H

Uimp: 6kV;

Ui: 500V;

Ue: B1N: AC240V(1P), AC415V(2P, 3P), DC60V(1P appearance), DC125V(2P appearance);

B1H: AC240V(1P), AC415V(2P, 3P);

In:

B1N: 0.5A, 1A, 1.6A, 2A, 3A, 4A, 5A, 6A, 7A, 8A, 10A, 13A, 15A, 16A, 20A, 25A, 30A, 32A, 35A, 40A, 45A, 50A, 60A, 63A;

B1H: 0.5A, 1A, 1.6A, 2A, 3A, 4A, 5A, 6A, 7A, 8A, 10A, 13A, 15A, 16A, 20A, 25A, 30A, 32A;

Over-current release: Thermal-magnetic;

Ics: 7.5kA;

Icu: 10kA;

1P, 2P, 3P;

IP30 (Except for terminals)

Selectivity category: A;

Applicable for isolation;

50/60Hz;

Auxiliary contact: 1NO1NC, Alarm contact: 1NO1NC

Ith: 6A;

Ue/Ie:

AC-12: AC480V/3A, 277V/3A, 240V/6A;

DC-12: DC250V/0.5A, 125V/1A, 48V/2A, 24V/6A;

Electronic Accessories complied with Annex N:

Undervoltage Release: AC/DC48V, AC240V

Page 1 of 1

Additional information (if necessary)

Date: Dec.07,2020

Signature:



Lu Mei